



TECNOELETTRA
SINCE 1985

BATTERY CHARGER

5A - 12VDC / 2,5A - 24Vdc

1570401S - 1570402S



Features:

- Protections: short-circuit / overload / over voltage
- Cooling by free air convection
- Led indicator for power on
- Built-in DC OK relay contact
- No load power consumption < 0.75 W
- 100% full load burn-in test
- Small dimensions: H90 x W40 x D100
- 3 years warranty

Mounting on DIN bar:

The module must be mounted in vertical position.

	UNIT	1570401S	1570402S
OUTPUT CURRENT	A	5	2,5
OUTPUT VOLTAGE	Vdc	12-15	24-30
DC VOLTAGE ADJUSTABLE	-	Yes	Yes
INPUT VOLTAGE RANGE	Vac	85-264	85-264
INPUT FREQUENCYRANGE	Hz	47-63	47-63
EFFICIENCY (AT FULL LOAD)	%	86	88
WORKING TEMPERATURE	°C	-20/+70	-20/+70
STORAGE TEMPERATURE	°C	-40/+85	-40/+85
WIDTH	mm	40	40
HEIGHT	mm	90	90
DEPTH	mm	100	100
WEIGHT	Kg	0,33	0,33

ORDER CODES	Vdc	Amp
1570401S	12	5
1570402S	24	2,5

The images in the catalogs are purely indicative and Tecnoelettra reserves the right to apply, in any moment and without notice, changes even structural to the product.



INNOVATION IS
OUR PASSION



THE EXCELLENCE
OF ITALIAN DESIGN

ITALY
Via Dimo Vioni,5 - Guastalla (RE) - 42016
Phone: +39 0522.832004
Fax : +39 0522.832012
E-Mail : info@tecnoelettra.it
www.tecnoelettra.it