



TECNOELETTRA
SINCE 1985

BATTERY CHARGER

2A - 12Vdc

1570401D



Features:

- Nominal input voltage: 115-230 Vac 57-63Hz
- Protection against overload and short-circuit
- IP20 protection rating
- DIN rail mounting (1 module)
- 2 years warranty

Signalling LED:

- Battery powered

Product code: 1570401D

	UNIT	CB2-1M
OUTPUT CURRENT	A	2
OUTPUT VOLTAGE	Vdc	13,8
DC VOLTAGE ADJUSTABLE	-	no
INPUT VOLTAGE RANGE	Vac	95-250
INPUT FREQUENCT RANGE	Hz	47-63
EFFICIENCY (AT FULL LOAD)	%	85
WORKING TEMPERATURE	°C	-10/+50
STORAGE TEMPERATURE	°C	-25/+85
WIDTH	mm	71
HEIGHT	mm	95
DEPTH	mm	73
WEIGHT	Kg	0,20

The images in the catalogs are purely indicative and Tecnoelettra reserves the right to apply, in any moment and without notice, changes even structural to the product.



INNOVATION IS
OUR PASSION



THE EXCELLENCE
OF ITALIAN DESIGN

ITALY
Via Dimo Vioni,5 - Guastalla (RE) - 42016
Phone: +39 0522.832004
Fax : +39 0522.832012
E-Mail : info@tecnoelettra.it
www.tecnoelettra.it